

Thermistor Probe Cloud-Connected Temperature Data Logger

- Measures temperature between -40 to +125 °C/-40 to +257 °F using a 75mm length barrel temperature probe on a 3m cable.
- Records and uploads temperature data to the EasyLog Cloud
- Access live temperature data via any Internet Browser or the App
- Set up alarm options for temperature zone breaches – email alerts, beeper alarms or LED flash alerts
- Suitable for indoor and outdoor use
- Battery life of up to 2 years



The LASREC058 kit has been designed to monitor temperature in a large range of applications, using a 75mm length barrel temperature probe on a 3m cable. Ideal for measuring ambient temperatures, the LASREC058 is suitable for monitoring environments such as offices, warehousing and greenhouses.

Products in the MOTE range are simple to set-up and easy to use. Download the App and set-up a device in minutes over your WiFi network. After set-up, the device can be placed anywhere within range of the WiFi network, continually monitoring and recording your data to the EasyLog Cloud. Access your data on any Internet Browser or the App, enabling you to monitor the ambient temperature of your chosen location from anywhere at any time.

MOTE devices can be programmed with high and low temperature alarm zones. If a temperature zone is breached, an alarm will be activated. Alarm options include: email alerts (which can be sent to one or multiple email addresses), beeper sound alarms, and LED flash alerts.

MOTE devices can be powered using the supplied batteries or a mains adapter (sold separately), and are provided with a wall mountable bracket for installation.

EasyLog Cloud

Your Data. Anytime. Anywhere.

EasyLog Cloud harnesses the power of IoT to automate data logging and alert notifications, enabling you to monitor and manage multiple data logging devices in different locations completely remotely. The system easily scales to meet your needs. Perfect for compact systems with just a few measuring points, or corporate solutions with thousands of devices around the globe.

You will need to create an account at www.easylogcloud.com before setting up your cloud-connected data logger.



Features at a glance*



Store your data logging records securely on the Cloud



Connect multiple users with variable account privileges



Connect data loggers from multiple sites in a single account



Easily access your most important data, anywhere



Remotely manage all of your data logging devices



Never miss a critical event with flexible advanced notifications



Review and analyse your data with powerful graphing functionality



Keep track of data events and system activity with a detailed event log

*Features depend on account type.

Thermistor Probe Cloud-Connected Temperature Data Logger

| Logger Specification | Minimum | Typical | Maximum | Unit |
|--|--|---------|------------|-------------|
| Battery Life | | 2* | | years |
| Battery Type | 4 x 1.5V AA cells | | | |
| Operating Temperature (Powered by Batteries Supplied) | -18 (-0.4) | | +55 (+131) | °C (°F) |
| Operating Temperature (Mains Adapter Powered) | -20 (-4) | | +60 (+140) | °C (°F) |
| Logging Period (User Configurable) | 10 sec | 10 min | 12 hrs | |
| Transmission Period (User Configurable) | 1 min | 1 hour | 24 hours | |
| Dimensions | 93 x 93 x 32 mm (3.7 x 3.7 x 1.3 inches) | | | mm (inches) |
| IP Rating | 67 | | | |

| Probe Specification | Minimum | Typical | Maximum | Unit |
|---------------------|--------------------------------|--|--|----------------------------|
| Range | -40 to +1250 (-4 to +257) | | | °C (°F) |
| Resolution | 0.1 (0.1) | | | °C (°F) |
| Accuracy | | ±0.8 (-15 to +70) (±1.5 (+5 to +158)) | ±1.5 (-40 to +125) (±3.0 (-40 to +257)) | °C (range) (°F (range)) |
| Probe Length | Probe barrel: 75 x 5 (3 x 0.2) | | | mm (inches) |
| Cable Length | 3000 (118) | | | mm (inches) |

The sensor is IEEE 802.11bgn (2.4GHz) compliant, supports WEP, WPA/WPA2 encryption and enterprise networks (PEAP, TTLS, FAST).



* Battery life is dependent on: transmission period, WiFi encryption method, WiFi encryption key rotation frequency (determined by the router/access point), signal strength between router/access point and WiFi device, presence, volume and type of WiFi traffic from other devices, sample rate and operating temperature. Logging period and transmission period can be configured in Settings via the EasyLog Cloud App.

WHAT'S IN THE BOX?

| PART | DESCRIPTION |
|---------------------|--|
| WALL BRACKET | Wall Mounting Bracket for EL-MOTE Device |
| BATTERIES | 1.5V AA x 4 |
| MOTE-P-TP | Thermistor Probe, 3m Cable, 75mm Barrel |

WHAT EXTRA ACCESSORIES ARE AVAILABLE?

| PART | DESCRIPTION |
|---------------------|--|
| MOTE-PSU | Mains Power Adapter |
| MOTE-P-TP | Thermistor Probe, 3m Cable, 75mm Barrel |
| WALL BRACKET | Wall Mounting Bracket for EL-MOTE Device |

Specifications liable to change without prior warning



CALIBRATION CERTIFICATES AVAILABLE

TIPTEMP offers a Traceable Calibration Certificate Service on Temperature Data Loggers using reference equipment traceable to national or international standards. For more information please see www.tiptemp.com/Products/Calibration-Equipment-and-services/