


Fast Response Thermocouple Assemblies



- Measure Temperature Surfaces!
- NIST Calibration Certificate Available. See page 13
- Lead wire available with Stainless Steel Overbraid.
- Quantity Discounts Available. See Page 2

HOW TO ORDER

Select **OUTLINED** Text To Create Part Number

STYLE

Select T/C Calibration

Select Termination

WTC - Washer Thermocouple

Standard Termination

20 awg. wire, Solid

LENGTH

Termination #3

- Choose #8, #10 and 1/4" screw sizes
- Choose GG (Fiberglass), TT (Teflon) or SSOB (Stainless Steel Overbraid)
- Choose Length.

Example

* GG = 20 gauge, Rated to 900°F (482°C)
 * TT = 20 gauge, Rated to 500°F (260°C)

1" to 12" Length = \$8.00
 13" to 36" Length = \$10.00
 37" to 72" Length = \$12.00
 73" & up add .50¢ per foot

6TC - SIX Pack of Wire Thermocouples

- Choose 20 awg - 24 awg - 30 awg - 36 awg
- Choose TTeflon or FiberGGlass insulation
- 60" length is standard. Add .60¢ per ft.

Example

\$85.00 per 6 pack
 Available with any plug, jack, or lug attached.

CONTINUE
 To Complete Part Number

\$55.00 PER 6 PACK

Stikon Adhesive & Non-Adhesive Thermocouple

.75

36"

Peel Sheet

.75

Carrier

Lead wire

\$18.00 each

Adhesive	Specifications	Non-Adhesive
Carrier	Kapton	Kapton
Total Thickness	0.017 inch	0.017 inch
Carrier Thickness	0.001 inch	0.001 inch
Cement Type	Silicone	
Adhesion	20 oz/inch	
Breaking Strength	30 lbs. / inch	
Operating Temp.	-100° to 500°F	-300° to 500°F
Size Of Carrier	0.75" x 0.75"	0.37" x 0.75"
Lead Wire Material	#30 ga. solid, PFA Teflon	#30 ga. solid, Fiberglass
Lead Wire Length	36"	36"

Stikon Non-Adhesive SNA

Stikon Adhesive SA

CONTINUE
 To Complete Part Number

Ordering Example: 6TC-24-GG-60-K-3

6TC = Six pack of Wire T/C's, 24 = 24 gauge wire, GG = Fiberglass insulation, 60" = wire length, K = Calibration, 3 = mini plug attached.

J
 + Iron
 - Constantan

1
 \$6.00 Large Plug

T
 + Copper
 - Constantan

2
 \$6.00 Large Jack

E
 + Chromel
 - Constantan

3
 \$6.00 Mini Plug
 Use 24 awg or smaller

4
 \$6.00 Mini Jack
 Use 24 awg or smaller

K
 + Chromel
 - Alumel

5
 \$4.00 T/C Alloy lugs

6
 Standard Leads
 \$N/C

K
 CALIBRATION

3
 TERMINATION